

Product Profile

Product



Overview

The RITE-SENSOR® from Bartec is a fully configurable and programmable universal sensor. Complete with an aluminium Clamp-in and black Snap-on valve stems, and work with all Bartec TPMS tools. Designed to replace faulty sensors, without the extra costs of having to buy expensive OE sensors. Ability to cover a high percentage of vehicles with Direct TPMS systems.

Kit contains: RITE-SENSOR® assembled with a rubber valve stem, optional aluminium valve stem, anti-rotational pin, User Guide.

Technical Specification

Nut Torque: 35.4in-lbsScrew Torque: 12.39in-lbs

Frequency 433 MHz

Sensor valve is warranted for 24 months*

Dimensions: 83 x 56 x 24 mm

Weight: 52g

*If the tyre is removed, the valve must be serviced to uphold the sensor lifetime warranty.

 ϵ

Product Images User Guide Fedrical Support 440 (p) 1224 77 881 Fedri

Product Benefits

- RITE-SENSOR® comes assembled with a rubber snap-in valve
- An aluminium Clamp-in stem is included, assembly is required
- Designed for optimum compatibility with OE and aftermarket wheels - no adjustment necessary
- Easy use with Bartec TPMS Tools: TECH350, TECH450 and TECH600
- Single part number SKU to reduce stock
- Extensive range of vehicle coverage
- One price for universal sensor enables fitter to have one price for fitting
- Save time and reduce complexity of TPMS one-stop-shop service
- The sensor can be programmed before or after installing for the specific vehicle
- A TPMS vehicle is required to complete the installation